

Meyn vent cutter ECP







Mode			12x8″	15x8″	16x6"	16x6"	20x6"	20x6″
Capac	ity	ВРН	6,000	9,000	8,000	8,000	8,500	12,000
Live w	reight	kg	2.5-5.5	2.5-5.5	0.5-1.7	1.2-4.0	0.5-1.7	1.2-4.0
Numb	er of units		12	15	16	16	20	20
Shack	le pitch	inch	8"	8"	6"	6"	6"	6"
Lengh	t (L)	mm	1,980	2,180	1,980	1,980	2,180	2,180
Width	(W1)	mm	780	970	780	780	970	970
Width	(W2)	mm	1,450	1,650	1,450	1,450	1,650	1,650
Width	(W3)	mm	2,450	2,850	2,450	2,450	2,850	2,850
Heigh	t (H)	mm	2,800	2,800	2,800	2,800	2,800	2,800
Weigh	t	kg	1,220	1,230	1,245	1,245	1,250	1,250
Water	connection	BSP	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Water	consumption	m ³ /h	1.0	1.0	1.0	1.0	1.0	1.0
Drain	connection	BSP	DN100	DN100	DN100	DN100	DN100	DN100

Head office:

Meyn Food Processing Technology B.V. Westeinde 6, 1511 MA Oostzaan (Amsterdam) P.O. Box 16, 1510 AA Oostzaan The Netherlands **T**: +31 (0)20 2045 000 **F**: +31 (0)20 2045 001 **I**: www.meyn.com



Meyn vent cutter ECP

- No yield loss or back damage as result of exact drilling position and sophisticate bird handling.
- Large weight range can be processed within one machine setting.
- Intestine damage is reduced to an absolute minimum.
- Effective cleaning of the drill unit after each cycle.







